


2
Safety Tester

Precision HI-POT Tester

7630/7631



Key Feature

- 2/9 channels (7630/7631)
- Graphic LCD
- Built-in programmable PLC remote control interface
- Built-in discharge circuit

- AC/DC hipot and insulation test
- Arcing detection
- Built-in RS-232 and USB Device
- Adjustable ramp time
- True RMS measurement circuit

Accessory

- Standard**
- Power cord
 - User manual CD
 - HV Test Cable

- Optional**
- RS-232 Cable
 - Remote Cable
 - 8/16 Channels Expansion Box (7508/7516)
 - D-Sub Footswitch (F760001)

Display Range

AC Withstand	10V-5000V	Insulation Resistance	10V-1000Vdc
DC Withstand	10V-6000V	Arcing	0-20

Specification

Measuring Item	Range	Resolution	Accuracy
AC Output Voltage	10V-5000V	1	±(3% of setting + 5V)
AC Output Frequency	50 / 60Hz	-	-
AC Upper Threshold (mA)	0.001-30	0.001	±3%
AC Lower Threshold (mA)	0-30.99	0.001	±3%
AC Measuring Time / Ramp Time	0.1-999s / 0.1-10s	0.1	-
AC Arcing	0-20	-	-
DC Output Voltage	10V-6000V	1	±(3% of setting + 5V)
DC Upper Threshold (mA)	0.001-5	0.001	±3%
DC Lower Threshold (mA)	0-4.99	0.001	±3%
DC Measuring Time / Ramp Time	0.1-999s / 0.1-10s	0.1	-
DC Arcing	0-5	-	-
IR Output Voltage	10-1000Vdc	1	±(3% of setting + 5V)
IR Upper Threshold (MΩ)	1-12000	1	100-500V, 1-1000MΩ (±5%) 500-1000V, 2-12000MΩ (±5%)
IR Lower Threshold (MΩ)	0-11999	1	
IR Measuring Time / Ramp Time	0.1-999s / 0.1-10s	0.1	-

General

Power Supply	Voltage	90~264Vac
	Frequency	50 / 60Hz ± 5%
Display	480*272, 4.3" TFT LCD	
Interface	RS-232, PLC Remote, USB Host, USB Device, EXT IO	
PLC Remote Control	Test, Abort	
PLC Output Signal	Pass / Fail / HV output / Testing	
Flash Memory	30 sets	
Multi-steps Mode	16 steps	
Environment	Temperature: 5 ~ 40°C, Humidity: 0 ~ 80%RH	
Dimension (W*H*D)	365x145x430 mm.....7630	
	435x145x500 mm.....7631	
Weight	14 Kg7630	
	15 Kg7631	